

ULTRATUFF Acrylic Sealer

PRODUCT:

ULTRATUFF Sealer is a Styrene Acrylic emulsion is supplied in 20Litre containers. Acrylic Sealer is a fast dry sealer, providing excellent adhesion to a wide variety of substrates.

Suggested Uses:

As a sealer for most water based conventional and high build coatings, Gib board, Concrete block, cementitious plasters, renders, brick, hard board, particle board, plywood.

PROPERTIES:

Non flammable & Low odour, waterbased Film possess excellent water and alkali resistance. SG:1kg/litre Minimum application temperature - + 10°C. Finish Semi gloss. Colour Milky liquid

Dry Times:

Touch dry: 60 minutes Recoat 2 hours

APPLICATION:

Surface Preparation

Surface must be clean and sound, free from oils, dust, chalk mildew and any other contaminants. If any of these are present then remove accordingly, either by scraping, sanding or power washing.

Thinning:

Clean potable water, concrete, brick, plaster etc, 1 part sealer, 1 part water
Gib board, particle board, plywood etc, 2 parts sealer, 1 part water

Application Method:

Brush, roller.

Avoid low surface/air temperatures as well as high humidity as this will increase drying time and curing rate. Do not apply below 10°C or above 85% relative humidity.
Ensure adequate air movement.

Coverage Rates:

8m²/litre/coat Note: 2 coats may be required on porous substrates.

Cleaning:

Wash up in water immediately after use.

For safety see the Material Safety Data Sheets:

All information is given in good faith without warranty. Users are encouraged to assess the product under their own conditions and for their own applications

Shelf Life:

24 months in unopened containers.

Flash Point:

None.

NZ Dangerous Goods Class:

Not applicable.